



ДЖИ ОЙЛ ЕКСПЕРТ ЕООД

Оторизиран дистрибутор за България

Мобил.0886 316656

office@goilexpert.com

www.goilexpert.com

<http://www.goilexpert-online.com/>

АВТОМАТИЗИРАНО УПРАВЛЕНИЕ НА ОХЛАЖДАЩАТА ТЕЧНОСТ

FluidWorker® 50 Автоматично измерва и контролира концентрацията и обема на флуида. Подобрява производството и работната среда, като същевременно намалява разходите, например за химикали и инструменти.

General Specification

Concentration range and accuracy	2-15%±1% (BRIX sensor)
Fluid volume	200-5 000L
Concentrate per month	<200L
Recommended fluids	Emulsions & micro-emulsions
Concentrate viscosity	5-200cSt at 40°C
BRIX cleaning system	Automatic

Monitoring & Interface

Human Machine Interface, HMI	5" colour touch screen
Weekly data / consumption	Concentration, Temp / Water
Network connection	OPC-UA, Ethernet (M12 D)
Update & log	USB

Mechanical & Electrical

Weight / Weight including packing.	14,8 kg / 17,3 kg
Concentrate hose length	4 m
IP-Class	IP 21
Max ambient and fluid operating temperature	45°C
Water hose length (included)	2 m, ½" female
Incoming water pressure	2.5-10 bar
Power supply/consumption	230V 1-phase, 50 Hz/5-25W
Electrical cable length	3.7 m

Accessories

Concentrate tank	30L with magnetic bracke
Signal tower	green yellow red, 5m cable



FluidWorker® 50 инсталиран на резервоар за охлаждаща течност

